

			UNIT	PL-CS												
				CS2M-38	CS2M-50	CS4-38	CS4M-50	CS4M-60	CS6-38	CS6M-38	CS6-50	CS6-50PP	CS6-60	CS8-38	CS8-50	CS8-60
成型组规格 MOLDING	合模力	Clamping force	kg	16000	16000	48000	48000	48000	60000	60000	60000	60000	60000	72000	72000	72000
	模具行程	Clamping stroke	mm	130	130	130	130	130	130	130	130	130	130	130	130	130
	拉杆行程	Stretching stroke	mm	320	320	320	320	320	320	320	320	320	320	320	320	320
	底模行程	Bottom stroke	mm	50	50	50	50	50	50	50	50	50	50	50	50	50
	瓶子间距	Cavity pitch	mm	120	120	120	120	120	120	120	120	120	120	120	120	120
	模穴数	Number of cavities	cavities	2	2	4	4	4	6	6	6	6	6	8	8	8
瓶型规格 CONTAINER	瓶子容量	Max container volume	ltr	1.5	1.5	1.6	1.5	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6
	牙部尺寸	Neck diameter range	mm	30	30-38	30	30-38	50	30	30	30-38	30-38	50	30	30-38	50
	瓶身直径	Max container diameter	mm	105	105	105	105	105	105	105	105	105	105	105	105	105
	瓶身高度	Max container height	mm	320	320	320	320	320	320	320	320	320	320	320	320	320
	胚头数	Carriage unit	pcs	92	75	108	95	76	120	120	126	288	100	162	160	136
单穴理论产能		Theoretical output (per cavity)	bph	1100	1000	1500	1000	800-1000	2000	1000-1200	1500	600-800	1500	2250	1200-1500	800-1000
电力规格 ELECTRICAL SYSTEM	总耗电量	Total power	KW	38	38	50	50	43	50	50	48	57	71	78	50	48
	加热功率	Heating power	KW	33	33	46	46	33	46	46	43	48	66	70	40	110
	灯管配置	Max heating power	KW	66	66	66	66	66	66	66	108	96	132	108	82	97
空压规格 AIR SYSTEM	操作压力	Operation pressure	kg/cm ²	7	7	7	7	7	7	7	7	7	7	7	7	7
	低压耗气量	Air consuming	ltr/min	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000
	吹瓶压力	Blowing pressure	kg/cm ²	35	35	35	35	35	35	35	35	16-25	35	35	35	35
	高压耗气量	Air consuming	ltr/min	2600	2600	8000	5500	8000	8000	6000	8000	6300	8000	12000	12000	10000
冷冻机规格 CHILLED WATER	操作压力	Operation pressure	kg/cm ²	4	4	4	4	4	4	4	4	4	4	4	4	4
	温度范围	Temperature	℃	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12
	消耗量	Consuming	kcal/hr	5400	5400	10000	10000	10000	12000	12000	12000	12000	12000	18000	18000	18000
	流量	Flow rate	ltr/min	30	30	60	45	60	60	60	60	60	40	160	160	100
冷却水规格 COOLING WATER	操作压力	Operation pressure	kg/cm ²	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4
	温度范围	Temperature	℃	30	30	30	30	30	30	30	30	30	30	30	30	30
	消耗量	Consuming	kcal/hr	30000	30000	54000	54000	54000	54000	54000	54000	54000	54000	104000	104000	104000
	流量	Flow rate	ltr/min	100	100	150	150	150	150	150	150	150	150	347	347	347
机台规格 MACHINE	机台尺寸	Machine size	mm	W 3500 D 1650 H 2600	W 3500 D 1650 H 2600	W 4480 D 1750 H 2600	W 4480 D 1650 H 2600	W 4700 D 1650 H 2600	W 5260 D 1800 H 2600	W 5260 D 1800 H 2600	W 6100 D 1900 H 2600	W 10000 D 1870 H 2600	W 6600 D 1900 H 2600	W 6600 D 1900 H 2600	W 7300 D 2035 H 2600	W 7500 D 1950 H 2850
	机台重量	Machine weight	kg	4000	4000	7000	7000	7500	8000	8000	8000	14000	8500	10000	11500	10000

			UNIT	PL-CS		PL-C				PL-CL				PL-CLL			PL-L1G								
				CS8M-50	CS8-50-D	C4-50	C5-50	C6-38	C6-50	CL2-60-II	CL3-60	CL4-60	CL5-76	CL6-60	CLL2-76	CLL3-76	CLL3M-76	L1G-90	L1G-76	L2G-90	L2G-76	L2G-120	L1G-76-D	L2G-76-D	
成型组规格 MOLDING	合模力	Clamping force	kg	72000	72000	64000	64000	72000	72000	30000	70000	70000	105000	105000	70000	105000	128000	64000	64000	128000	128000	128000	64000	128000	
	模具行程	Clamping stroke	mm	130	130	160	160	160	160	210	210	210	240	210	240	240	320	320	320	320	320	320	320	320	
	拉杆行程	Stretching stroke	mm	320	320	350	350	350	350	350	350	350	420	350	420	420	500	500	500	500	500	500	500	500	
	底模行程	Bottom stroke	mm	50	50	30	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	50	
	瓶子间距	Cavity pitch	mm	120	120	160	160	160	160	200	200	200	200	200	260	260	270	-	-	320	320	320	-	320	
	模穴数	Number of cavities	cavities	8	8	4	5	6	6	2	3	4	5	6	2	3	3	1	1	2	2	2	1	2	
瓶型规格 CONTAINER	瓶子容量	Max container volume	ltr	1.6	1.6	3	3	3	3	5	5	5	5	5	10	10	15	12-20	12-20	12-20	12-20	12-20	12-20	12-20	
	牙部尺寸	Neck diameter range	mm	38	38	38	38	30	38	30-50	30-50	30-50	50-60	30-50	60	60	60	72	55	72	55	100	55	55	
	瓶身直径	Max container diameter	mm	105	105	130	130	130	130	175	175	175	175	175	210	210	230	290	290	290	290	290	290	290	
	瓶身高度	Max container height	mm	320	320	350	350	350	350	350	350	350	420	350	420	420	500	500	500	500	500	500	500	500	
	瓶头数	Carriage unit	pcs	160	210	124	110	162	160	78	107	107	80	122	71	106	97	52	85	52	85	96	71	82	
单穴理论产能			Theoretical output (per cavity)	bph	500-700	1200-2000	800-1000	1000-1100	900-1000	900-1000	1200	1200	1200	800	1000	800	800	400-600	450-600	400-600	450-600	400-600	400-600	700-800	600-800
电力规格 ELECTRICAL SYSTEM	总耗电量	Total power	KW	50	100	90	68	78	78	72	45	58	58	58	74	75	75	40	52	40	48	75	75	68	
	加热功率	Heating power	KW	40	86	80	60	70	70	66	40	53	53	53	66	70	70	36	40	36	44	66	66	57	
	灯管配置	Max heating power	KW	82	216	132	108	108	108	132	99	132	132	98	122	117	120	60	80	60	92	132	132	114	
空压规格 AIR SYSTEM	操作压力	Operation pressure	kg/cm²	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	
	低压耗气量	Air consuming	ltr/min	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	1000	2000	2000	2000	2000	2000	
	吹瓶压力	Blowing pressure	kg/cm²	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35	35	
	高压耗气量	Air consuming	ltr/min	8000	12000	8000	10000	12000	12000	6000	9500	12500	15000	15000	12500	14840	20400	6800	6800	13600	13600	13600	7200	19000	
冷冻机规格 CHILLED WATER	操作压力	Operation pressure	kg/cm²	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
	温度范围	Temperature	℃	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	10-12	
	消耗量	Consuming	kcal/hr	18000	18000	12000	15000	18000	18000	7000	12000	12000	15000	15000	15000	15000	15000	26040	26040	26040	26040	26040	26040	26040	
	流量	Flow rate	ltr/min	160	160	100	100	160	160	60	90	90	90	90	90	100	100	100	100	100	100	100	100	100	
冷却水规格 COOLING WATER	操作压力	Operation pressure	kg/cm²	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	2-4	
	温度范围	Temperature	℃	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	30	25	25	25	
	消耗量	Consuming	kcal/hr	104000	104000	54000	60000	90000	90000	30000	54000	54000	54000	54000	54000	78000	78000	78000	78000	78000	78000	78000	78000	78000	
	流量	Flow rate	ltr/min	347	347	150	150	200	200	150	150	150	150	150	150	150	150	260	260	260	260	260	260	260	
机台规格 MACHINE	机台尺寸	Machine size	mm	W 7300 D 2035 H 2600	W 8500 D 2035 H 2600	W 5920 D 1870 H 2600	W 6000 D 1900 H 2600	W 6600 D 1900 H 2600	W 7300 D 2035 H 2600	W 4250 D 1850 H 2600	W 6500 D 1850 H 2600	W 6500 D 1850 H 2600	W 7000 D 1850 H 2600	W 8000 D 1850 H 2600	W 4700 D 2100 H 3500	W 5000 D 3000 H 3500	W 6200 D 3000 H 3200	W 4300 D 3000 H 3200	W 5300 D 3000 H 3200	W 4500 D 3000 H 3200	W 5500 D 3000 H 3200	W 5300 D 2960 H 3700	W 4690 D 2100 H 3300	W 5520 D 2100 H 3300	
	机台重量	Machine weight	kg	11500	12000	10000	10000	10000	12000	8000	10000	10000	12000	12000	9000	12000	13000	10000	11000	12000	13000	12000	7000	9000	